

XHZ Series Style Air Gripper



MHZ2-25D

Ordering Code

XHZ

Model
XHZ: Parallel fingers
XHZL: Long stroke
finger

2

**Finger
Quantity**
2PCS

16

Bore Size
6mm~40mm

D

Action Type
D: Double Action
S: Single Action
(Normally open)
C: Single-Action
(Normally closed)

1

Claw Form
Blank: Standard Basic Type
1: Side screw installation
2: Opening and closing direction
through-hole installation
N: Narrow basic type
N1: Side screw hole installation
N2: Opening and closing direction
through hole installation

Graphic Symbol



Double-acting-internal grip



Double-acting-External grip



Single acting normally
closed-Internal grip



Single acting normally
closed-External grip

Specification

Bore(mm)		6	10	16	20	25	32	40
Working Medium	Air (to be filtered by 40 µm filter element)							
Operating pressure	Double-action	0.15~0.7	0.2~0.7				0.1~0.7	0.1~0.7
	Single-action	0.3~0.7	0.35~0.7				0.25~0.7	0.25~0.7
Ambient fluid temperature	-10~60°C							
Repeatability(mm)	±0.01						±0.02	
The highest frequency of use	180(XHZL Series 120)(c.p.m)						60(c.p.m)	
Lubrication	Not required							
Action type	Double acting-Single acting							
Auto switch(optional)	Solid state auto switch							
Port size	M3×0.5				M5×0.8			

Gripping force


Model	Gripping force N				Opening/Closing (Both sides)mm
	RMS each finger gripping force				
	Double-acting		Single acting	Single acting	
	External	Internal	External	Internal	
XHZ-6□	3.3	6.1	1.9	3.7	4
XHZ-10□	11	17	7.1	13	4
XHZ-16□	34	45	27	38	6
XHZ-20□	42	66	33	57	10
XHZ-25□	65	104	45	83	14
XHZ-32□	158	193	131	161	22
XHZ-40□	254	318	217	267	30

Model	Gripping force N				Opening/ Closing (Both sides)mm
	RMS each finger gripping force				
	Double-acting		Single acting	Single acting	
	External	Internal	External	Internal	
XHZL-10□	11	17	7.1	13	8
XHZL-16□	34	45	27	38	12
XHZL-20□	42	66	33	57	18
XHZL-25□	65	104	50	85	22


□ = Express D=Double-acting S=Single acting(normally closed) C=Single acting(normally open)

XHZ Series Style Air Gripper


Overall Dimensions




XHZ-6 □ (Φ6)
Double acting
Single acting




Auto switch mounting groove dimensions




For single acting, the port on one side will turn into breathing hole.




XHZ-10 □
Auto Switch Mounting Groove Dimensions




Note) Through-hole mounting is not possible when using the auto switch at the square groove.



XHZ-□□ (Φ10~Φ40)
Double acting
Single acting



XHZ-□□
Auto Switch Mounting Groove Dimensions



Note) Through-hole mounting is not possible when using the auto switch at the square groove.

For single acting, the port on one side will turn into breathing hole.

XHZ Series Style Air Gripper


Dimension Sheet

Bore(mm)	A	B	C	D	E	F	G	H	I	J	K	K1	K2	K3	ΦL	M	N	O	P	Q	
10	6	23	12	37.8	57	29	15.2 ^{+2.2} ₀	11.2 ⁰ _{-0.7}	4 ⁰ _{-0.1}	16	M3×0.5	6	5.5	6	2.6	27	Φ11H9 ^{+0.043} ₀	Dp2	11.4	M2.5×0.45	3
16	7.5	24.5	15	42.5	67.3	38	20.9 ^{+2.2} _{0.2}	14.9 ⁰ _{-0.7}	5 ⁰ _{-0.1}	24	M4×0.7	4.5	8	8	3.4	30	Φ17H9 ^{+0.043} ₀	Dp2	16	M3×0.5	4
20	9.5	29	20	52.8	84.8	50	26.3 ^{+2.2} _{0.2}	16.3 ⁰ _{-0.7}	8 ⁰ _{-0.1}	30	M5×0.8	8	10	10	4.3	35	Φ21H9 ^{+0.052} ₀	Dp3	18.6	M4×0.7	5
25	11	30	25	63.6	102.7	63	33.3 ^{+2.5} _{0.2}	19.3 ⁰ _{-0.8}	10 ⁰ _{-0.1}	36	M6×1	10	12	12	5.1	36.5	Φ26H9 ^{+0.052} ₀	Dp3.5	22	M5×0.8	6
32	12	40(49)	29	67(76)	113(122)	97	48 ^{+2.5} _{0.2}	26 ⁰ _{-0.5}	12 ⁰ _{-0.1}	46	M6×1	10	13	13	5.1	48(57)	Φ34H9 ^{+0.052} ₀	Dp4	26	M6×1	7
40	15	49(62)	36	83(96)	139(152)	119	60 ^{+2.7} ₀	30 ⁰ _{-0.5}	14 ⁰ _{-0.1}	56	M8×1.25	13	16	17	6.6	58(71)	Φ42H9 ^{+0.052} ₀	Dp4	32	M8×1.25	9


Bore(mm)	R	S	T	U	V	W	X	Y	Z	Y1	Y2	AA	BB	CC	DD	EE	
10	5.7	M3×0.5	23	9	19	5 ⁰ _{-0.05}	11	Φ2H9 ^{+0.025} ₀	Dp:3	16.4±0.05	5.2±0.02	7.6±0.02	18	12	-	-	
16	7	M5×0.8	30.6	7.5	19	8 ⁰ _{-0.05}	13	Φ3H9 ^{+0.025} ₀	Dp:3	23.6±0.05	6.5±0.02	11±0.02	22	15	11.6	2.1	5.8
20	9	M5×0.8	42	10	23	10 ⁰ _{-0.05}	15	Φ4H9 ^{+0.03} ₀	Dp:4	27.6±0.05	7.5±0.02	16.8±0.02	32	18	14	2.1	9
25	12	M5×0.8	52	10.7	23.5	12 ⁰ _{-0.05}	20	Φ4H9 ^{+0.03} ₀	Dp:4	33.6±0.05	10±0.02	21.8±0.02	40	22	19	3.5	11.5
32	14	M5×0.8	60	11	31(37)	15 ⁰ _{-0.05}	24	Φ5H9 ^{+0.03} ₀	Dp:5	40±0.1	12±0.02	23±0.02	46	26	24	3.3	11.5
40	17	M5×0.8	72	12	38(45)	18 ⁰ _{-0.05}	28	Φ5H9 ^{+0.03} ₀	Dp:5	48±0.1	14±0.02	29±0.02	56	32	29.4	3.7	13

Overall Dimensions

XHZL-□□ (Φ10~Φ25)
Double acting
Single acting




XHZL-10□
Auto Switch Mounting Groove Dimensions



Note) Through-hole mounting is not possible when using the auto switch at the square groove.

XHZL-□□
Auto Switch Mounting Groove Dimensions



Note) Through-hole mounting is not possible when using the auto switch at the square groove.

Dimension Sheet

Bore(mm)	A	B	C	D	E	F	G	H	I	J	K	K1	K2	K3	ΦL	M	N	O	P	Q	
10	6	25(35)	12	37.8(47.8)	57(67)	35	19.2 ^{+2.2} ₀	11.2 ⁰ _{-0.7}	4 ⁰ _{-0.1}	16	M3×0.5	6	5.5	6	2.6	29(39)	Φ11H9 ^{+0.043} ₀	Dp2	11.4	M2.5×0.45	3
16	7.5	31(36)	15	45.2(50.2)	70(75)	47	26.9 ^{+2.2} _{0.2}	14.9 ⁰ _{-0.7}	5 ⁰ _{-0.1}	24	M4×0.7	4.5	8	8	3.4	36(41)	Φ17H9 ^{+0.043} ₀	Dp2	16	M3×0.5	4
20	9.5	36(42)	20	58(64)	90(96)	62	34.3 ^{+2.2} _{0.2}	16.3 ⁰ _{-0.7}	8 ⁰ _{-0.1}	30	M5×0.8	8	10	10	4.3	43(49)	Φ21H9 ^{+0.052} ₀	Dp3	18.6	M4×0.7	5
25	11	40(50)	25	66.9(76.9)	106(116)	75	41.3 ^{+2.5} _{0.2}	19.3 ⁰ _{-0.8}	10 ⁰ _{-0.1}	36	M6×1	10	12	12	5.1	48(58)	Φ26H9 ^{+0.052} ₀	Dp3.5	22	M5×0.8	6

Bore(mm)	R	S	T	U	V	W	X	Y	Z	Y1	Y2	AA	BB	CC	DD	EE	
10	5.7	M3×0.5	23	8	21(31)	5 ⁰ _{-0.05}	11	Φ2H9 ^{+0.025} ₀	Dp:3	16.4±0.05	5.2±0.02	7.6±0.02	18	12	-	-	
16	7	M5×0.8	30.6	8	25(30)	8 ⁰ _{-0.05}	13	Φ3H9 ^{+0.025} ₀	Dp:3	23.6±0.05	6.5±0.02	11±0.02	22	15	11.6	2.1	5.8
20	9	M5×0.8	42	10	30(36)	10 ⁰ _{-0.05}	15	Φ4H9 ^{+0.03} ₀	Dp:4	27.6±0.05	7.5±0.02	16.8±0.02	32	18	14	2.1	9
25	12	M5×0.8	52	10	33(43)	12 ⁰ _{-0.05}	20	Φ4H9 ^{+0.03} ₀	Dp:4	33.6±0.05	10±0.02	21.8±0.02	40	22	19	3.5	11.5