





Power [kW]	Duty Cycle	Base speed [rpm]	Base freq. [Hz]	Base voltage Δ [V]	Absorb. Δ [A]	Base voltage Y [V]	Absorb. Y [A]	 Teknomotor S.r.l. Via Argenegea 31, I-32038 Quero Vas (BL) www.teknomotor.com
2.2	S1	18000	300	220	8.6	380	5.0	
Power [kW]	Duty Cycle	Base speed [rpm]	Base freq. [Hz]	Base voltage Δ [V]	Absorb. Δ [A]	Base voltage Y [V]	Absorb. Y [A]	
6000	18000	300	IP54	F	COM41470241	Min speed [rpm] Max speed [rpm] Max freq. [Hz] Protection Ins. Cl. Part number on nameplate		
Balancing according to ISO 1940 - G2.5 @ 18000 rpm		Balancing type		cool type  full key cool type  half key	Peso / weight	Title		
					6.52 kg	4147-C-SB-P-ER20-RH		
rev. n°	description			date	signature	Customer	Drawing code	
01	Ventola da D.14 a D.10mm			12/04/2017	E. Gaspari	Catalogo	COM41470241	
00	Emissione			02/04/2014	D. Bottarel	Tolleranze non quotate: UNI EN 22768 fH Smussi non quotati: 0.5 mm Rugosità secondo UNI ISO 1302		
drawn - date	approved - date	checked - date	sostituisce il	dis. n°1333 cod. 5Com41470241.dwg		foglio / sheet	scala	
E. Gaspari - 12/04/2017	S. Perli - 12/04/2017	S. Perli - 12/04/2017	sostituito dal			1 / 1	1:2	