



Power [kW]	Duty Cycle	Base speed [rpm]	Base freq. [Hz]	Base voltage Δ [V]	Absorb. Δ [A]	Base voltage Y [V]	Absorb. Y [A]
3.3	S1	18000	300	220	13.7	380	7.9
Power [kW]	Duty Cycle	Base speed [rpm]	Base freq. [Hz]	Base voltage Δ [V]	Absorb. Δ [A]	Base voltage Y [V]	Absorb. Y [A]
Min speed [rpm]		Max speed [rpm]	Max freq. [Hz]	Protection	Ins. Cl.	Part number on nameplate	
6000		24000	400	IP54	F	COM51600453	
Balancing according to ISO 1940 - G2.5 @ 24000 rpm		Balancing type		foot type full key	foot type half key	Peso / weight	Title
						12.89 kg	5160-A-2DB-P-ER32-HY-RH
rev. n°	description			date	signature	Customer	Drawing code
00	Emissione			12/04/2019	D. Bottarel	Catalogo	COM51600453
						Tolleranze non quotate: UNI EN 22768 fH Smussi non quotati: 0.5 mm Rugosità secondo UNI ISO 1302	
drawn - date	approved - date	checked - date	sostituisce il		foglio / sheet	scala	A4
D. Bottarel - 12/04/2019	S. Perli - 12/04/2019	S. Perli - 12/04/2019	sostituito dal		1 / 1	n.d.	

**TEKNOMOTOR**

Teknomotor S.r.l.  
Via Argeneva 31, I-32038 Quero Vas (BL)  
www.teknomotor.com