








传感器插头线 SENSOR PLUG WIRE

类型 Structural category	直形孔座接插电缆 接插件M8×1		弯形孔座接插电缆 接插件M8×1		弯形孔座接插电缆 接插件M8×1	直形孔座接插电缆 接插件M12×1	
外形编号Outward Appearance code	RK01-1-2	RK01-1-3	RK01-2-2	RK01-2-3	RK01-2-2-4	RK01-2-3-4	RK02-1-2
外形图例 Outward appearance illustration							
外形尺寸 Overall dimensions							
接插外形 CONTACT VIEW							
应用 APPLICATION	DC二线 AC二线 NO/NC	NPN/PNP NO/NC	DC二线 AC二线 NO/NC	NPN/PNP NO/NC	DC二线 AC二线 NO/NC	NPN/PNP NO/NC	DC二线 AC二线 NO/NC
接插件 Connector	黑Black Cu Zn, nickel plated						
外套颜色 Skind color							
连接螺母材料 Coupling nut material							
接触负载 Contact load							
过流值 Over-current value(A)							
额定电压 Rated voltage(V)							
电缆 Wire 长度 Length							
电缆外皮材料 Cable jacket material							
绝缘体颜色 insulator color							
输出显示 (LED) output diplay (LED)							
通电指示 power indicator	bu, bu, bk 3×0.5						
一般数据 common data	bu, bu 2×0.5						
绝缘电阻 insulation resistance	Black, bu, bu 2×0.5						
环境温度范围接插件 environment temperature scope(°C)	1						
环境温度范围 电缆 environment temperature scope(°C)	-						
防护等级 (DIN 40 050) protection level	-						
电容率 Capacotance	≥10 ³ Ω -25...+80 -25...+80						
	IP67 250VAC/300VDC, Gr.C						

传感器插头线

SENSOR PLUG WIRE

类型 Structural category		直形孔座接插电缆 接插件M12×1					弯形孔座接插电缆 接插件M12×1			
型号 Type		RK02-1-3	RK02-1-4	RK02-2-2	RK02-2-3-N	RK02-2-3-P	RK02-2-4-N	RK02-2-4-P	RK03-3	RK03-4
外形图例 Outward appearance illustration										
外形尺寸 Overall dimensions										
接插件外形 CONTACT VIEW										
应用 APPLICATION		NPN/PNP NO/NC	NPN/PNP NO/NC	DC二线 AC二线 NO/NC	NPN NO/NC	PNP NO/NC	NPN NO/NC	PNP NO/NC	NPN/PNP NO/NC	NPN/PNP NO/NC
接插件 Connector		黑Black Cuzn, nickel plated 4.0 250 2m PVC								
外套颜色 Skind color										
连接螺母材料 Coupling nut material										
接触负载 Contact load										
过流值 Over-current value(A)										
额定电压 Rated voltage(V)										
电缆 Wire 长度 Length										
电缆外皮材料 Cable jacket material										
绝缘体颜色 insulator color										
输出显示 (LED) output diaplay (LED)		bu, bu, bk 3×0.5	bu, bu, bk, wh 4×0.34	YES	YES	YES	YES	YES	YES	YES
通电指示 power indicator		-								
一般数据 common data		-								
绝缘电阻 insulation resistance		≥10 ⁹ Ω								
环境温度范围接插件 environment temperature scope(°C)		-25…+65								
环境温度范围电缆 environment temperature scope(°C)		-25…+65								
防护等级 (DIN 40 050) protection level		IP67								
电容量 Capacotance		250VAC/300VDC, Gr.C								